Description	Unit	Dimensions
Pump pressure	Bar	10*
Water volume Qmax	l/hout	4500*
Max. recommended temp. of input water	°C	30
Effective jet length from nozzle	m	15*
Dimensions L x W x H	Mm	2800 x 1500 x 1800
Weight with empty buffer tank	Kg	800
Voltage	V	380
Buffer tank for water supply	ltr.	400
1" hose for water supply	m	15
Electrical cable for power supply	m	15
Power plug	-	16 amp. CEE
Nozzle size, long distance nozzle	mm	6,4

* = 2,2 kW pump

Operating time and water consumption estimate

The figures in the table are only intended as a guide, as the figures may vary from machine to machine. The tests were carried out with a standard 6.4 mm nozzle and 2.2 kW pump.

House Width	Speed (%)	Speed of hose uncoiling (cm/min)	Speed of uncoiling (m/h)
20-25 meters	15 / 20 / 25	33 / 44 / 57	20 - 26 - 34
15-19 meters	30 / 35	72 / 82	43 / 49
10-14 meters	40 / 45	98 / 110	59 / 66
Soaking only	50 / 100	120 / 250	72 / 150

House dimensions		Speed	Operating time	Water consumption m³		
Width	Length	m/h	h	9 bar	4 bar	3,75 bar
15	90	63	1,43	6,4	4,6	4,1
18	90	51	1,76	7,9	5,7	5,1
21	90	36	2,5	11,3	8,1	7,2
24	90	36	2,50	11,3	8,1	7,2
24	110	36	3,06	13,8	9,9	8,8

House dimensions		Speed	Operating time	Water consumption m3			Water consumption (l/per. m2 floor)		
Bredde	Længde	m/t	t	9 bar	4 bar	3,75 bar	9 bar	4 bar	3,75 bar
15	90	63	1,43	6,4	4,6	4,1	4,76	3,43	3,05
18	90	51	1,76	7,9	5,7	5,1	4,9	3,53	3,14
21	90	36	2,5	11,3	8,1	7,2	5,95	4,29	3,81
24	90	36	2,50	11,3	8,1	7,2	5,21	3,75	3,33
24	110	36	3,06	13,8	9,9	8,8	5,21	3,75	3,33